



REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PRODUCT RELEASE	TOM	2011.03.22

- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS
    - CONTACT RESISTANCE: 80 milliohms MAX.
    - INSULATION RESISTANCE: 1,000 Megohms MIN.
    - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
  - MECHANICAL CHARACTERISTICS
    - RETENTION FORCE: MIN.100gf/PIN
    - DURABILITY: 5,000 CYCLES
  - RoHS 2002/95/EC COMPLIANT.

B	CONTACT	6	COPPER ALLOY 0.15t	Gold plated on contact area Gold plated on Solder tail All over Nickel Plated .
A	HOUSING	1	HIGH-TEMPERATURE PLASTIC UL94-V0	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				<b>AUGO</b> 精致元器件 TITLE: SIM CARD 6P SIMPLE TYPE (10.0*7.60) PART NO. <b>BC-25-6PD180</b> DWN TOM 2011.03.22 CHKD APVD SCALE 1:1 UNIT: mm SIZE: A4 SHEET: 10F1 REV: A
DECIMALS: ANGLES: X :±0.5 X :±2° X.X :±0.3 X.X :±1° X.XX :±0.2				
CUSTOMER COPY				

DIMENSION INFORMATION

DIM.A	P/N
1.80	BC-25-6PD180